(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁷: G01S 5/00, 5/14

(21) International Application Number: PCT/EP00/13120

(22) International Filing Date:
21 December 2000 (21.12.2000)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants *(for all designated States except US)*: NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI). VUORISALO, Miika [FI/FI]; Pellervonkatu 9 A 703, FIN-33540 Tampere (FI).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: NUUTINEN, Pan [FI/FI]; Nokia Corporation, Keilalahdentie 4, FIN-02150 Espoo (FI). MAANOJA, Markus [FI/FI]; Nokia Corporation, Keilalahdentie 4, FIN-02150 Espoo (FI).

(74) Agents: LESON, Thomas, Johannes, Alois et al.; Bavariaring 4, 80336 München (DE).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND SYSTEM FOR TRANSFERRING GPS DATA IN MOBILE NETWORK

(57) Abstract: The invention proposes a method and system for transferring location Data in a mobile network, preferably for assisting in locating one or more Mobile Station(s) in the network, the network comprising at least one receiver outputting raw location data, and at least one location entity. The raw location data are transferred from the receiver to the location entity using one or more signalling protocol(s), e.g. LLP. The location entity is adapted to process the received raw location data so as to generate assistance data which are transferred to the mobile station. The invention is preferably used in a network-assisted mobile-based GPS location method and system allowing to detect the present location of a Mobile Station.

METHOD AND SYSTEM FOR TRANSFERRING
GPS DATA IN MOBILE NETWORK

DESCRIPTION OF THE INVENTION

FIELD AND BACKGROUND OF THE INVENTION

The invention generally refers to the locating of Mobile
Station(s) in networks such as cellular communications
networks. The term "Mobile Station(s)" as used here intends
to cover all types of mobile devices such as mobile phones,
portable computers, User Equipment(s) (UEs) etc.

In particular, but not exclusively, the invention relates to
network-assisted mobile based GPS location method and system
allowing to detect the present location of a Mobile Station
(MS). For performing such a location method, GPS assistance
data are necessary from the network. These GPS assistance
data are usually directly sent to the MS from the base
station e.g. in a positioning measurement request.

When, however, as an example, a SMLC (Serving Mobile Location
Centre) should be adapted to generate the GPS assistance data
for MS (Mobile Station), the SLMC needs raw GPS satellite
data for generation of the GPS assistance data. Transfer of
the generated GPS assistance data from SMLC to MS can be
implemented in accordance with standardized information
transmission to a MS, for instance by including this GPS
assistance data in a position measuring request. Problems

however arise with regard to the acquisition of raw GPS
satellite data by SMLC.

5   SUMMARY OF THE INVENTION

The invention provides a method and/or system as defined in
the independent claims or any of the dependent claims.

10   The invention generally provides a method and system to
transfer raw location data, e.g.GPS data, (i.e. subframes) in
telecom network.

The invention is also applicable to, and intends to cover,
15   networks of other types such as 3G (Third Generation)
networks and IP-RAN (Internet Protocol-based Radio Access
Network), where SMLC is integrated in SRNC (Serving Radio
Network Controller).

20   According to a preferred embodiment of the invention,
one or more of the signalling protocols, e.g. LLP, of the
communication network are used to transfer the raw location
data, preferably GPS satellite data (subframes) from source
(e.g. BS or LMU) to SMLC(s) which uses this data e.g. for
25   generating GPS assistance data e.g. for MS. Communication
network may consist of e.g. core network and radio network.
The used signalling protocol preferably is a location service
protocol such as LLP protocol (LMU LCS Protocol).

30   Preferably, one or more dedicated reference receivers, e.g.
GPS receivers, are provided on known location (e.g. in LMU
(Location Measurement Unit) on BTS-site) which send raw
location data, e.g. GPS subframes, to one or more SMLCs
through already existing communication network (e.g. Abis).

2

The SMLC(s) may be assigned to e.g. a BTS (Base Transceiver Station) and/or a certain reference area. The reference receiver(s) is/are raw data source of this particular reference area.

5

The SMLC(s) therefore need not be equipped with own GPS receiver or reference GPS receiver.

The SMLC(s) may send acquired raw GPS satellite data in
10 communication network (e.g. through the core network) to other SMLC(s) which have no direct connection to reference GPS receiver. The SMLC(s) may send this raw GPS satellite data to the other SMLC(s) using one or more signalling protocol(s) of the telecom network. The signalling protocol
15 used by the location entity to transfer the raw location data to the another location entity may be a control protocol, e.g. SMLCPP (SMLC Peer Protocol).

20   BRIEF DESCRIPTION OF THE DRAWINGS

        Fig. 1 illustrates an embodiment in accordance with the present invention with 2G terms, and

25   Fig. 2 shows the signal flows and method steps of an embodiment in accordance with the present invention.

        DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE
30   INVENTION

Fig. 1 shows an embodiment of the invention and illustrates a reference GPS network. Fig. 1 shows a plurality of Reference GPS areas (2) (three reference GPS areas 1,2,3 are shown)

3

which are supplied with GPS signals (raw data) from a
plurality of satellites (1). Each reference GPS area (2)
comprises at least one BTS (Base Transceiver Station) (3).

5   Each reference GPS area comprises one (or more) dedicated
reference GPS receiver which receives signals from at least
four satellites (1) as represented by dotted lines. This GPS
receiver is arranged at a known location, preferably in LMU
(Location Measurement Unit) on the site of the BTS (3) of

10 this reference GPS area. The reference GPS receiver(s) is/are
GPS raw data source of this particular reference GPS area and
transmits this GPS raw data (e.g. sub-frames) to one or more
SMLC assigned to the same reference GPS area as the GPS
receiver. A storage and/or processing means (5) included in,

15 or cooperating with, its assigned SMLC (4) stores and/or
processes the received GPS raw data so as to generate GPS
assistance data for Assisted GPS allowing Network Assisted
GPS Support e.g. as defined by respective standards such as
ETSI. The manner of generation of GPS assistance data from

20 raw GPS satellite data is known per se and can be used in the
SMLC (4) in a similar or identical manner as e.g. in a base
station (BS) or LMU (Location Measurement Unit) or the like.

The GPS subframes (raw data) are sent from the reference GPS
25 receiver to the SMLC(s) (4) through already existing telecom
network or backbone (e.g. Abis). The dot-and-dash lines
represent GPS rawdata transfer from reference GPS receiver to
SMLC (4).

30 Each BTS (3) is assigned to at least one BSC (Base Station
Controller) (6) for handling the communication between the
network entities such as BTS (3), SMLC (4), and MSC (Mobile
Switching Centre) (7) interconnecting the reference GPS areas
and cells. As shown in Fig. 1, reference GPS area 1 comprises

two BSCs (6) whereas the other reference GPS areas include only one BSC (6).

When SMLCs (4) of different areas or cells intend to
5   communicate with each other, e.g. for transferring GPS raw data or assistance data, the connection is established via MSC (7). The dashed lines represent the GPS rawdata transfer between SMLCs (4).

10   In Fig. 1, interfaces (protocols) are named like in 2G (Second Generation) type networks, but the invention intends to cover also other types of networks (e.g. 3G and All-IP). All of those protocols can be used to transfer raw GPS data. In accordance with one of the preferred aspects of this
15   embodiment of the invention, GPS reference data are transported from LMU (3) to SMLC (4) over the existing standardised interface. As an example shown in Fig. 1, LLP protocol can be used for transporting the GPS reference data (or GPS raw data) from LMU to SLMC (4)(LLP means "LMU LCS
20   Protocol", LCS stands for "Location Service").

For communication between SMLCs (4) e.g. via MSC (7), SMLCPP (SMLCPP, SMLC Peer Protocol) is preferably used.

25   A basic feature of this embodiment is thus to use the signalling protocols of the communication network to transfer raw GPS satellite data (subframes) from source (e.g. Base Station or SMLC (4)) to SMLC(s) (4) which use the data for generation of GPS assistance data for an MS (Mobile Station).
30
In another embodiment, the interface between SMLC (4) and MSC (7) may e.g. be the Ls-interface. Signaling on the Ls interface may e.g. use BSSAP-LE. The interface between BSC (6) and SMLC (4) can be a Lb-interface. The signalling on

this interface may likewise use BSSAP-LE. The interface
between Peer SMLCs (4) can e.g. be an Lp-interface. Both NSS
and BSS-based SMLCs (4) may support the Lp interface to
enable access to information and resources owned by another
5 SMLC (4). Signalling on this interface may likewise use
BSSAPP-LE, or SMLCPP.

The GPS receivers preferably are installed within 100 to 300
km radius. Since base stations (BSs) have fixed co-ordinates,
10 the GPS receiver(s) may preferably be positioned e.g. in or
at a LMU (Location Measurement Unit) on BS-site. BS can then
send GPS subframes to SMLC (4) through already existing
interface (e.g. Abis, Lub).

15 As an example, GPS raw data from each satellite are subframes
(each 300 bit), and GPS raw data sending rate from satellite
is 50 bit/s. The needed transfer rate for 12 satellites
rawdata will then be 600 bit/s (75 byte/s). Calculations and
simulations show that these data and data rates can be
20 transferred using the teaching of the present invention
without problems. These data can be transferred e.g. through
Q1 interface.

Fig. 2 illustrates method steps and data flow in an
25 embodiment of the invention such as the one shown in Fig. 1.
A satellite (1) sends GPS raw data to a reference GPS
receiver (10) installed e.g. in the base station or BTS (3)
of reference GPS area (2). The GPS receiver (10) transfers
this GPS raw data in unprocessed or eventually preprocessed
30 form to the SMLC (4) via a signalling protocol of the
communication network. The data sent from receiver (10) to
SMLC (4) may additionally include error correction (or
indication) data for correcting or indicating location

6

detection errors detected by the GPS reference receiver so as
to form a Differential GPS (DGPS) system.

The SMLC (4) performs a data processing step 12 for deriving
5   Assistance GPS data from the received GPS raw data. This
Assistance GPS data may then be sent to one or more mobile
stations (11) attached to the communications network
including one or more of the BTSs (3).

10   Further, as shown in Fig. 2, the SMLC (4) may transmit the
GPS raw data (and/or the Assistance GPS data) to another SMLC
(4) using an appropriate signalling protocol of the
communication network.

15   The invention may e.g. be used in network assisted MS based
GPS location in different products in different generations
(e.g. in 2G, in 3G or in All IP).

Using existing cellular signalling backbone in accordance
20   with a preferred implementation of the invention is an easy,
reliable and economical solution for delivering GPS data.
Technically the idea can be implemented e.g. by using or
extending SMLCPP protocol similarly to RIT (Radio Interface
Timing) information exchange.
25
Although the invention has been described above with
reference to specific embodiments, the invention likewise
covers any modifications, amendments, omissions etc of the
above teaching.

CLAIMS

1. Method for transferring location information in a
mobile network, preferably for assisting in locating one or
more Mobile Station(s) in the network, the network comprising
at least one receiver outputting raw location data, and at
least one location entity,
wherein the raw location data are transferred from the
receiver to the location entity using one or more signalling
protocol(s).

2. Method according to claim 1, wherein the location
information is received from a GPS system.

3. Method according to claim 1 or 2, wherein the raw
location data is GPS raw data.

4. Method according to any one of the preceding claims,
wherein the location entity processes the received raw
location data so as to generate assistance data, preferably
GPS assistance data.

5. Method according to claim 4, wherein the location
entity transfers the assistance data to the mobile station.

6. Method according to any one of the preceding claims,
wherein the location entity is a SMLC (Serving Mobile
Location Centre).

7. Method according to any one of the preceding claims, wherein the mobile Station is a mobile phone, portable computer, or User Equipment (UE).

5   8. Method according to any one of the preceding claims, wherein the network is a cellular communications networks.

9. Method according to any one of the preceding claims, wherein the signalling protocol is a signalling protocol of

10   the communication network.

10. Method according to any one of the preceding claims, wherein the signalling protocol is a signalling protocol used in core network.

15

11. Method according to any one of the preceding claims, wherein the signalling protocol is a signalling protocol used in radio network.

20   12. Method according to any one of the preceding claims, wherein the signalling protocol is   location service protocol.

13. Method according to claim 12, wherein the location

25   service protocol is LLP protocol (LMU LCS Protocol).

14. Method according to any one of the preceding claims, wherein the location entity transfers the raw location data to another location entity using one or more signalling

30   protocol(s).

15. Method according to any one of the preceding claims, wherein the signalling protocol used by the location entity to transfer the raw location data to the another location

35   entity is control protocol.

16. Method according to claim 15, wherein the control
protocol is SMLCPP (SMLC Peer Protocol).

5   17. Network-assisted mobile based location method,
preferably GPS location method, allowing to detect the
present location of a Mobile Station (MS), wherein the method
uses a method according to any one of the preceding claims.

10   18. System for transferring location information in a
mobile network, preferably for assisting in locating one or
more Mobile Station(s) in the network, the system comprising
at least one receiver outputting raw location data, and at
least one location entity,
15   wherein the receiver is adapted to transfer the raw location
data to the location entity using one or more signalling
protocol(s).

19. System according to claim 18, wherein the location
20   information is received from a GPS system.

20. System according to claim 18 or 19, wherein the raw
location data is GPS raw data.

25   21. System according to any one of claims 18 to 20,
wherein the location entity is adapted to process the
received raw location data so as to generate assistance data,
preferably GPS assistance data.

30   22. System according to claim 21, wherein the location
entity is adapted to transfer the assistance data to the
mobile station.

23. System according to any one of the preceding system claims, wherein the location entity is a SMLC (Serving Mobile Location Centre).

5   24. System according to any one of the preceding system claims, wherein the Mobile Station is a mobile phone, portable computer, or User Equipment (UE).

25. System according to any one of the preceding system
10   claims, wherein the network is a cellular communications networks.

26. System according to any one of the preceding system claims, wherein the signalling protocol is a signalling
15   protocol of the communication network.   .

27. System according to any one of the preceding system claims, wherein the signalling protocol is a signalling protocol used in core network.
20

28. System according to any one of the preceding system claims, wherein the signalling protocol is a signalling protocol used in radio network.

25   29. System according to any one of the preceding system claims, wherein the signalling protocol is location service protocol.

30. System according to claim 29, wherein the location
30   service protocol is LLP protocol (LMU LCS Protocol).

31. System according to any one of the preceding system claims, wherein the location entity is adapted to transfer the raw location data to another location entity using one or

more signalling protocol(s).

32. System according to any one of the preceding system claims, wherein the signalling protocol used by the location
5   entity to transfer the raw location data to the another location entity is control protocol.

33. System according to claim 32, wherein the control protocol is SMLCPP (SMLC Peer Protocol).

10

34. Use of the system according to any one of the preceding system claims in a network-assisted mobile based location system, preferably GPS location system, allowing to detect the present location of a Mobile Station (MS).

FIG. 1

GPS signal from
satellite

GPS rawdata
transfer from
reference receiver
to SMLC

GPS rawdata
transfer between
SMLCs

FIG. 2

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MA

IPC 7   G01S5/00   G01S5/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7   G01S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 56143 A (SNAPTRACK INC) 4 November 1999 (1999-11-04)	1-5, 7-13, 17-22, 24-30
Y	page 3, line 24 -page 4, line 13 page 10, line 24 -page 11, line 26 page 17, line 31 -page 19, line 27 claims 6,7 ---	6,23
X	US 6 067 045 A (CASTELLOE MICHAEL ET AL) 23 May 2000 (2000-05-23) column 3, line 50 - line 64 column 6, line 11 -column 7, line 2 ---	1-3,7, 17-20, 23,24,34
X	WO 99 54753 A (ERICSSON INC) 28 October 1999 (1999-10-28) page 6, line 25 -page 7, line 22 ---	1-8, 17-25

-/--

[X] Further documents are listed in the continuation of box C.   [X] Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
21 August 2001	30/08/2001

| Name and mailing address of the ISA
 European Patent Office, P.B. 5818 Patentlaan 2
 NL – 2280 HV Rijswijk
 Tel. (+31–70) 340–2040, Tx. 31 651 epo nl,
 Fax: (+31–70) 340–3016 | Authorized officer

 Ó Donnabháin, C |

Form PCT/ISA/210 (second sheet) (July 1992)

Category °	Citation of document, with indication,where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 00 69187 A (NOKIA MOBILE PHONES LTD ;NOKIA INC (US)) 16 November 2000 (2000-11-16)	6,23
A	abstract page 5, line 8 - line 14	1-5,7-34
A	WO 99 19743 A (ERICSSON GE MOBILE INC) 22 April 1999 (1999-04-22) Summary of the Invention page 6, line 13 -page 7, line 9	1-34

C.(Continuation) DOCUMENTS CONS   D TO BE RELEVANT

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9956143	A	04-11-1999	US 6185427	B	06-02-2001
			AU 4181099	A	16-11-1999
			AU 4181199	A	16-11-1999
			WO 9956144	A	04-11-1999
US 6067045	A	23-05-2000	EP 0984295	A	08-03-2000
			FR 2782868	A	03-03-2000
			GB 2343575	A	10-05-2000
WO 9954753	A	28-10-1999	AU 4307399	A	08-11-1999
WO 0069187	A	16-11-2000	AU 4815400	A	21-11-2000
WO 9919743	A	22-04-1999	US 6070078	A	30-05-2000
			AU 1086499	A	03-05-1999
			BR 9813061	A	22-08-2000
			CN 1276875	T	13-12-2000
			EP 1023612	A	02-08-2000
			NO 20001960	A	15-06-2000